



ATEN CL3000N

ProdCode: ATENCL3000N

Lightweight Single Rail LCD Console (PS/2-USB, VGA)



[Download Images] (.zip file)

Features

- Lightweight Single Rail LCD Console (PS/2-USB, VGA)
- Advanced Random Vibration Resistance Testing - MIL-STD-810G Certified
- Lightweight design for easier installation
- Exclusive LED illumination light - designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions
- Integrated KVM console featuring a 19" LCD monitor

The CL3000 Lightweight PS/2-USB LCD Console is a LCD KVM console that serves as the front end console for compatible KVM switches.

Lightweight and with a 19" power-saving LED-backlit LCD, the CL3000 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, LED-backlit LCD monitor, and touchpad in a 1U housing.

In addition, testing is performed utilizing the MIL-STD-810G* (Method 514.6, Procedure 1, Category 4 Common Carrier) procedure for Vibration Certification. MIL-STD-810G testing provides proven reliable operations of the CL3000 in harsh environments, by using advanced testing to emphasize the equipment's environmental design and limits in real world conditions that it will experience throughout its life; such as operating in a moving vehicle or on a factory floor where high vibrations occur often.

*MIL-STD-810G Method 514.6, Procedure I, Category4
(Common Carrier, US Highway Truck Vibration Exposure) Exposed to random vibration tests at different levels based on axes from 5 to 500Hz, for one hour per axis. Total levels applied are 1.07Grms vertical axis (Z axis), 0.76Grms transverse axis (Y axis), and 0.76Grms longitudinal axis (X axis)

Note: Optional rack mount kits are available.

In the box:

- 1x CL3000 Lightweight PS/2-USB LCD Console with Standard Rack Mounting Kit
- 1x Custom KVM Cable (VGA, USB, PS/2; 1.8m/6ft)
- 1x Power Cord
- 1x User Instructions

