



ATEN CL3800NW

ProdCode: ATENCL3800NW

Ultra Short Depth Dual Rail WideScreen LCD Console (USB, HDMI / DVI / VGA)



[\[Download Images\]](#) (.zip file)

Features

- Ultra Short Depth Dual Rail WideScreen LCD Console (USB, HDMI / DVI / VGA)
- Exclusive LED illumination light - designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions
- Integrated KVM Console with short depth dual rail design and a 18.5" LED-backlit LCD monitor allows you to work in narrow spaces
- Supports an external console with USB / DVI / VGA / HDMI connectors
- The 18.5" LCD screen offers resolutions of up to 1920 x 1080 (Full HD) @ 60Hz for CL3800NW and resolutions of up to 1366 x 768 @ 60Hz for CL3800NX

The CL3800 USB HDMI DVI VGA LCD Console is a short depth dual rail LCD KVM console featuring an 18.5" LED-backlit widescreen LCD monitor with an integrated keyboard and touchpad. The short-depth design fits all 19" equipment cabinets, and is especially suitable for shallow racks. In addition to saving valuable space on the rack, the CL3800 also provides a space-saving solution for special environments, such as outside broadcast vans (OB vans) and compact control rooms.

The CL3800 supports three types of video input – HDMI, DVI, and VGA – and provides the ultimate in installation flexibility by allowing users to connect the console and the computer via any of the three types of video source. The CL3800NW's full HD widescreen LCD monitor ensures excellent video quality and provides ample viewing area.

Furthermore, the dual rail design enables the LCD monitor, keyboard and touchpad to operate independently of each other. To maximize space utilization, the keyboard and touchpad modules can slide back to "hideaway" when not in use, while the thin profile LCD monitor rotates back, flush against the rack, to allow the convenient monitoring of computer activity.

For added convenience, users can choose to manage the computer from an external console. The CL3800 features a port for an external USB mouse on the unit's front panel, while ports for the second KVM console (USB keyboard/mouse and HDMI, DVI, or VGA monitor) are provided on the rear panel. The CL3800 also includes two mini stereo ports for connecting audio speakers.

With a rich feature set, the CL3800 is designed to exceed the requirements for space utility optimization, superior video quality, adaptive deployment, and operational versatility, and is ideal for applications such as mobile live streaming in the broadcasting sector or control rooms with limited space in any industry.

Note: Optional rack mount kits are available.

In the box:

- 1x CL3800 LCD KVM Console with Standard Rack Mount Kit
- 1x USB HDMI KVM Cable (HDMI, USB, Audio; 1.8 m/6 ft)
- 1x Firmware Upgrade Cable
- 1x Power Cord
- 2x L Brackets
- 1x User Instructions

