

ATEN PE6324LG

ProdCode: ATENPE6324LG

30A/32A 24-Outlet Metered & Switched Low Profile eco PDU



[Download Images] (.zip file)

Features

- 30A/32A 24-Outlet Metered & Switched Low Profile eco PDU
- Bank level power metering and monitoring
- Remote power outlet control (On/Off, Power Cycle) by individual outlets and outlet groups
- Support TCP/IP, UDP, HTTP, HTTPS, SSL, DHCP, SMTP, NTP, DNS, Auto Sense, Ping, Telnet, and SNMP V1,V2&V3
- Proactive Overload Protection (POP) automatically powers off outlets when current overloads to protect operating devices
- 0U 24-Outlet low profile eco PDU
- · Bank level metering
- Supports Proactive Overload Protection (POP) / Outlet Switch Control

The PE6324L PDUs are low-profile units featuring 24 AC outlets, coming available in various IEC or NEMA socket configurations. This series has a smaller input region on the PDU to provide more installation space for data centers.

The PE6324L eco PDUs offers remote power control with real-time power measurement - allowing users to monitor the power status of devices attached to the PDUs, either at the PDU device or Bank level, from practically any location via a TCP / IP connection. The power status of each outlet can be set individually, allowing users to switch each device On / Off.

This series supports any 3rd party v1, v2 & v3 SNMP Manager Software and ATEN eco DC (Energy & DCIM Management Web GUI), delivering an easy method for multiple device management while offering an intuitive and user-friendly GUI that allows users to configure a PDU device and monitor power status of the equipment connected to it.

In the box:

- 1x PE6324L eco PDU
- 1x Mounting Kit
- 1x User Instructions

