

Blackmagic Design DeckLink Duo 2 Mini

ProdCode: BMDBDLKDUO2LP

Compact, multi channel PCI Express capture and playback card that supports all SD and HD formats up to 1080p60

[Download Images] (.zip file)

Features

- Compact, multi channel PCI Express capture and playback card that supports all SD and HD formats up to 1080p60
- Features 4 independent mini 3G-SDI connections
- You get the flexibility of 4 separate capture or playback cards in one
- Completely customizable so it's perfect for media play-out systems, multi screen digital signage servers, real time multi channel capture systems and more

Connections

- **SDI Video Inputs** 4 x bidirectional 12-bit SD/HD independently configurable as either Input or Output.
- **SDI Video Outputs** 4 x bidirectional 12-bit SD/HD independently configurable as either Input or Output.
- SDI Audio Inputs 16 channels embedded in SD and HD.
- SDI Audio Outputs 16 channels embedded in SD and HD.
- Sync Input Tri-Sync or Black Burst.
- Computer Interface PCI Express 4 lane generation 2, compatible with 4, 8 and 16 lane PCI Express slots.

Supported Codecs

AVC-Intra, AVCHD, Canon XF MPEG2, Digital SLR, DV-NTSC, DV-PAL, DVCPRO50, DVCPROHD, DPX, HDV, HEVC, XDCAM EX, XDCAM HD, XDCAM HD422, DNxHR & DNxHD, Apple ProRes 4444, Apple ProRes 422 HQ, Apple ProRes 422, Apple ProRes LT, Apple ProRes 422 Proxy, Uncompressed 8-bit 4:2:2, Uncompressed 10-bit 4:2:2, Uncompressed 10‑bit 4:4:4

In the box:

- DeckLink Duo 2 Mini
- SD card with software and manual

