



Datavideo HBT-50

ProdCode: DATAHBT50

4-Channel HDBaseT Receiver with SDI and HDMI Outputs



[\[Download Images\]](#) (.zip file)

Features

- 4-Channel HDBaseT Receiver with SDI and HDMI Outputs
- Supplies power, video signal, and camera control up to 4 devices up to 100 meters distance
- Simultaneously output HDMI and SDI

An essential link to connect all your equipment for your live production

The HBT-50 supplies power, video signal, and camera control up to 4 devices up to 100 meters distance. It simultaneously outputs HDMI, SDI, RS-422 and IP control signals.

Add HDBaseT to your SDI Workflow seamlessly

HBT-50 can power the PTZ video cameras via PoE, transmit signals over a single ethernet cable to and from the camera and can be used to remotely control various camera parameters such as iris, presets and etc. Most importantly, it can output SDI signal to your switcher.

Integrate camera control, switcher and recorder operations

HBT-50 simultaneously transmits SDI (up to 1080p60) and HDMI (up to 1080p60) as well as camera control. With the HBT-50, the system can be integrated camera controller, video switcher, and ISO recorder.

Simultaneously outputs HDMI, SDI

HBT-50 provides outputs HDMI and SDI simultaneously. It is great us on long distance camera video transmitting to switcher, or ISO recorder. These is no need to prepare 4 additional HDBaseT receiver, HBT-50 will get the work done for it.

Perfect solution for your broadcast SDI workflow.

Remote control of camera functions via RS-422 or DVIP with SDI video transmission (up to 1080p50/60) and HDMI video transmission (up to 1080p50/60) up to 4 cameras simultaneously up to 100m.

In the box:

- 1x HBT-50 main unit
- 1x AC Cord

