

Datavideo HS-1600T Mark II

ProdCode: DATAHS1600TMKII

4-Channel HD/SD HDBaseT Portable Video Streaming Studio



[Download Images] (.zip file)

Features

- 4-Channel HD/SD HDBaseT Portable Video Streaming Studio
- Built-in H.264 web streaming encoder
- Built-in H.264 recorder for SD cards
- Built-in camera control interface for up to 3 Datavideo PTZ cameras
- Made with HDBaseT Technology
- 17.3" LED Backlit Monitor
- 4 video inputs: 3x RJ-45 & 1x HDMI
- 4 video outputs: 3x HDMI & 1x HDBaseT
- Audio inputs: 2x XLR Analogue & 2x RCA Analogue (L/R)
- Portable "briefcase" design

Made for mobility. Made for the web.

The HS-1600T Mark II brings a new level of simplicity to production workflows. You'll set up faster and easier thanks to its portable "briefcase" design and HDBaseT Technology. And thanks to its built-in H.264 web streaming encoder, you can stream your show to virtually any CDN like YouTube and Facebook in no time.

Variety of video and audio input/output

4 video inputs (RJ-45 x 3 + HDMI x 1) and 4 video (HDMI x 3)+HDBaseT outputs

Audio inputs: XLR Analogue x 2 + RCA Analogue (L/R) x 2

Made with HDBaseT Technology

Camera connections typically require one cable for video, a second cable for power, and a third one for control. However, the HS-1600T Mark II is able to do all of the above using only one ethernet cable for each camera. This increase in flexibility greatly reduces setup time, and now you can mount the camera in challenging locations (like spots without nearby power outlets).

Built-in H.264 recorder for SD cards

The HS-1600T Mark II comes with a built-in web-ready recorder. Simply insert your SD card, and you'll have video files that can be immediately uploaded to the video network of your choice or to your website.

Dual Stream encoder to Facebook Live, YouTube, Twitch, and more

With the built-in H.264 streaming encoder, you can stream your show to two different streaming platforms virtually any CDN including Facebook, YouTube or Twitch in no time.

Built-in camera control.

The HS-1600T Mark II's next generation design saves you time, money, and table space with its built-in camera control interface for up to 3 Datavideo PTZ cameras. (Works with PTC-140T and PTC-150TL)

17.3" LED Backlit Monitor

Built-in Monitor Display. 17.3" HD TFT LED backlit monitor with resolution 1920x1080 pix.

In the box:

- 1x HS-1600T Mark II
- 1x AD Switch DC 56V with AC Cord
- 3x Ethernet Cables (55in. / 140cm)

