



Ikan GA102D-PTZ

ProdCode: IKAGA102DPTZ

Aluminium PTZ Tripod w/ 100mm Flat Base & Dolly, Quick Release Plate, 88 lbs. Payload (E-Image)



[\[Download Images\]](#) (.zip file)

Features

- Aluminium PTZ Tripod w/ 100mm Flat Base & Dolly, Quick Release Plate, 88 lbs. Payload (E-Image)
- Mounts PTZ Cameras, PTZ Teleprompters, or Pan-Tilt Heads
- Tripod Kit Supports Up to 88 lbs.
- Height Range: 23.7" – 68.1"
- 2-Stage Legs w/ Mono-Lock Leg Locking System
- Includes EI-7004B Dolly w/ Locking Wheels and Cable Guard

Secure your PTZ Teleprompter or Robotic PTZ Head onto the GA102D-PTZ Tripod System's 100mm Flat Base. This tripod kit provides different mounting options for PTZ solutions including a PTZ camera, pan-tilt head, or a full PTZ teleprompter. With this studio version, you can transport your PTZ camera around the set or studio smoothly and quickly with the included EI-7003B dolly with cable guards.

Various PTZ Solutions

The GA102D-PTZ Tripod System is a versatile mounting solution tailored for PTZ equipment. Whether you're utilizing a PTZ camera, a robotic pan-tilt head, or a full PTZ teleprompter, this tripod system offers a 100mm flat base with a 3/8" – 20 mounting screw, ensuring secure and stable attachment of your equipment.

HEAVY-DUTY TRIPOD

The GA102 tiered video tripod legs are made of aluminium and can hold 132 lbs. The GA102 is topped off with a 100mm bowl for quickly adjusting the payload horizontally and/or vertically.

MONO-LOCK

The heavy-duty tripod is made of aluminium and the legs are a twin tube design with two stages. It includes the E-Image Mono-Lock design which allows you to control the height of both stages with a single twist lock.

FLAT BASE

The 100mm Flat Base includes a 3/8"-16 mounting screw at the top and is designed to mount PTZ Teleprompter Systems or Robotic PTZ Heads. When using the pedestal with our 19" PTZ Teleprompter system, the 100mm Flat Base provides additional preliminary tilt adjustment. This will help remove the teleprompter monitor from your camera shot if you're shooting at a wide focal length. After finalizing your preliminary tilt adjustment, your PTZ Camera can be used for primary panning & tilting adjustments moving forward. If you are looking to only mount the PTZ camera itself, the P6 quick-release plate is included and can also be mounted directly onto the 100BF flat base.

EI-7004B DOLLY

The EI-7004B dolly features 4" locking rubber wheels with a capacity of 132.3

pounds. This system has a working footprint of 39.4 inches and has height-adjustable cable guards. Each dolly system is easy to fold with its handle and single wingnut for transport in the DB-01 carrying bag (included).

In the box:

- 1 x P6 Quick Release Plate
- 1 x 100BF 100mm Flat Base
- 1 x GA102 Aluminum Tripod
- 1 x GS01 Mid-Level Spreader
- 3 x F3 Rubber Feet
- 1 x EI-7004B Dolly

