

Ikan M-PTZ-PEDESTAL

ProdCode: IKAMPTZPEDBUN

Motorized Pedestal for PTZ Cameras & Teleprompters



[Download Images] (.zip file)

Features

- Motorized Pedestal for PTZ Cameras & Teleprompters
- Silent Motorized Column with on-shot stroke of 25.6"
- 66 lbs Payload Capacity
- Height Range: 39.2?- 109.8?
- Heavy Duty QR Plate with Sliding Range of 4.17"
- Dolly with Cable Guards

The M-PTZ-PEDESTAL Motorized Elevation System is designed for PTZ cameras and PTZ teleprompters, offering smooth, motorized height adjustments and supporting up to 66 lbs of equipment for stable operation. It includes a wired remote controller capable of controlling the column using an up & down arrow button, or with quick preset position buttons. With the 2-stage legs and center column fully extended, you can shoot video at heights up to 9.1 ft. Whether using this pedestal for corporate AV offices, studio broadcast, or capturing a live performance, the M-PTZ-PEDESTAL offers the flexibility and performance to meet and exceed expectations.

Smooth Motorized Elevation | Remote-Control Convenience

At the heart of the M-PTZ-PEDESTAL is its smooth motorized elevation system, which allows effortless height adjustments with the simple push of a button. Operated via a wired remote controller equipped with a clear display screen, users can monitor and adjust elevation settings accurately in real-time. The remote-control convenience not only streamlines the shooting process but also minimizes physical input, enabling operators to focus on capturing the perfect shot without manual interference.

High Payload Capacity | Maximum Stability

With a payload capacity of 66lbs, not only can you mount a PTZ camera and accessories, but also Ikan's PTZ teleprompters. The robust construction guarantees that the equipment remains secure, providing peace of mind during critical shooting moments.

Extended Working Height

With a maximum working height of 9.2 feet when used with a dolly, the M-PTZ-PEDESTAL allows operators to capture unique shooting angles that add depth to the footage. After adjusting the height of the legs by-hand, the pedestal system features a motorized stroke of 23.6 inches, offering significant vertical movement to adapt to various shooting requirements, from low-angle shots to elevated viewpoints. The motorized column operates so smoothly that it can be used to create vertical camera movements suitable for live broadcasts.

Quick Positioning with Preset Height Positions

Efficiency is further enhanced by the system's ability to store and recall three preset height positions. This feature enables quick switching between frequently used elevations, saving valuable time during shoots that require repetitive positioning. The intuitive wired remote controller makes it easy to program and select these presets, ensuring consistent framing and composition across different takes.

Mono-Lock Mechanism

To speed up the setup process, the Mono-Lock feature simplifies height adjustments by allowing both tripod legs to be adjusted simultaneously with a single twist.

Quick-Release Adapter

This QR Adapter allows for quick and secure attachment of cameras. This quick-release mechanism enhances efficiency, particularly when swapping cameras or adjusting configurations on the fly.

Accessory Integration

The system includes standard 1/4? and 3/8? screw holes, providing the flexibility to attach various accessories such as monitors, microphones, or lights directly to the tripod. This integration reduces the need for additional stands and streamlines the overall equipment setup.

Enhanced Stability with Quick-Release Middle Spreader

M-PTZ-PEDESTAL provides stability with its quick-release middle spreader. This adjustable spreader enhances the tripod's rigidity, reducing vibrations and providing a solid foundation for the camera setup. The design allows for quick adjustments, enabling operators to set up and break down the system efficiently.

Extendable Up To 82ft

Optional Extension Cables are available in two different lengths, 8.2ft & 13ft. The pedestal system comes included with two 8.2ft cables, but an additional 82ft of extension can be achieved using these cables.

- 8.2ft Cable
- 13ft Cable

Expandable Functionality with Optional Accessories

The M-PTZ-PEDESTAL's versatility is further amplified through a range of optional accessories:

• MS-010: By combining the M-PTZ-PEDESTAL with the M-PED-DUAL-M

boom, operators can mount two PTZ cameras simultaneously. This setup is ideal for multi-angle shooting, live broadcasting, or any application requiring simultaneous camera operation.

- 260AC-03: This kit allows for seamless integration of a V-mount battery, providing a reliable power source for the motorized column and eliminating dependency on external power outlets.
- 260AC-01: This 2.4G Bluetooth remote controller can replace the wired remote controller and will operate at a max distance of 32ft.

In the box:

- 1x Motorized Tripod & Center Column
- 1x Quick Release Plate
- 1x EI-7004B Dolly
- 1x SC-4 Tripod Carrying Bag
- 1x Dolly Carrying Bag
- 1x Power Supply Unit
- 1x Power Supply Cable (3-Meter)
- 1x Motor Cable (2.5-Meter)
- 1x Motor Extension Cable (2.5-Meter)
- 1x Wired Remote Controller (2-Meter)
- 1x User Guide

