



Magewell Pro Convert AES67

ProdCode: MAGEPROCONAES67

Multi-format IP audio converter and capture device



[\[Download Images\]](#) (.zip file)

Features

- Multi-format IP audio converter and capture device
- Offers a seamless bridge between analog audio, software and IP standards including AES67, NDI®, SRT and more
- Provides a flexible, virtual audio matrix to allow routing or mixing of any analog or IP-based input channel to any output
- Enables mixed-technology local and remote production workflows and ProAV installations

Input/Receiving Features

Receiving up to 46 audio channels

- 1 x 2-channel 3.5mm unbalanced in
- 1 x 2-channel 4.4mm balanced in
- 1 x 4-channel 24-bit/48k UAC in
- Receiving 4 x 8-channel 24-bit AES67 streams both multicasted and unicasted
- It is optional to receive 1 x 4-channel 16-bit SRT stream or 1 x 4-channel 16-bit NDI® stream or 1 x 4-channel 16-bit Icecast stream

Output/Sending Features

- 1 x 2-channel 3.5mm unbalanced out
- 1 x 2-channel 4.4mm balanced out
- 1 x 4-channel 24-bit/48k UAC out
- Multicast and unicast up to 8 x 8-channel 24-bit AES67 streams
- Encoding 1 x 4-channel 16-bit audio for Icecast/SRT/NDI® stream simultaneously

Audio routing and mixing Features

- Any analogue or IP-based input channel can be routed and mixed into any analogue, IP or UAC output via a web-based user interface

Others

- Plug-and-play as a UAC device
- Provide comprehensive information regarding the device and signals in real-time
- Remote control via Web GUI and Control Hub
- Support USB RNDIS/ECM
- Provide HTTP APIs
- Provide Crestron Plugins

In the box:

- Pro Convert AES67
- 1x Power Adapter (US/EU/UK/AU/JP)
- 1x USB Type A to Type B cable
- 1x L bracket
- 1x 4.4mm to Dual XLR Male Cable
- 1x 4.4mm to Dual XLR Female Cable

