



Magewell Pro Convert Audio DX

ProdCode: MAGEPROCONAUDDX

Multi-format IP audio converter and capture device (Dante® enabled)



[\[Download Images\]](#) (.zip file)

Features

- Multi-format IP audio converter and capture device (Dante® enabled)
- Offers a seamless bridge between analog audio, software and IP standards including Dante®, NDI®, SRT and more
- Provides a flexible, virtual audio matrix to allow routing or mixing of any analog or IP-based input channel to any output
- Enables mixed-technology local and remote production workflows and ProAV installations

Input/Receiving Features

- 1 x 2-channel 3.5mm unbalanced in
- 1 x 2-channel 4.4mm balanced in
- 1 x 4-channel 24-bit/48k UAC in
- Receiving 8-channel 24-bit Dante® streams in unicast or multicast
- Receiving 2 x 4-channel 16-bit network audio streams of SRT and/or NDI® simultaneously

Output/Sending Features

- 1 x 2-channel 3.5mm unbalanced out

- 1 x 2-channel 4.4mm balanced out
- 1 x 4-channel 24-bit/48k UAC out
- Encoding 8-channel 24-bit Dante® streams in unicast or multicast
- Encoding 2 x 4-channel 16-bit network audio streams of RTSP, SRT, NDI® protocols simultaneously

Audio routing and mixing Features

- Any analogue or IP-based input channel can be routed and mixed into any analogue, IP or UAC output via a web-based user interface

Others

- Support for Dante Controller, providing signal routing and configuration
- Plug-and-play as a UAC device
- Provide comprehensive information regarding the device and signals in real-time
- Remote control via Web GUI and Control Hub
- Provide HTTP APIs

In the box:

- Pro Convert Audio DX
- 1x Power Adapter (US/EU/UK/AU/JP)
- 1x USB Type A to Type B cable
- 1x L bracket
- 1x 4.4mm to Dual XLR Male Cable
- 1x 4.4mm to Dual XLR Female Cable

