

Panasonic LUMIX S-R1635

ProdCode: PANSR1635E

LUMIX S PRO 16-35mm F4 Wide Zoom Full-Frame L Mount Lens

[Download Images] (.zip file)

Features

LUMIX S PRO CAMERA LENS

16-35mm wide angle zoom L-mount lens for LUMIX S Series Full-Frame digital mirrorless cameras

VIDEO SUPPORT

Excels in video recording performance with a mechanism to suppress focus breathing and micro-step aperture control for smooth exposure change

• LENS ELEMENTS

12 elements in 9 groups, the use of 3 aspherical lenses, an ED (Extra-low Dispersion) lens and a UHR (Ultra-High Refractive Index) lens with optimum alignment to achieve high MTF performance

RUGGED LENS DESIGN

Dust/splash*/freeze-resistant design withstands heavy field use under harsh conditions for high mobility (*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.)

FOCUS CLUTCH MECHANISM

Enables instant AF/MF switching, accurate manual focusing and suppressed focus breathing

The LUMIX S PRO 16-35mm F4 (S-R1635) is a versatile wide zoom lens that provides high resolution images despite its compact, lightweight profile. It boasts high descriptive performance in both photo shooting and video recording.

For the AF actuator, a double-magnet linear motor is integrated. It features high power despite its small size, achieving a maximum 480 fps high-speed sensor drive. This realizes fast, high-precision AF to ensure that photo opportunities are never missed. Adoption of a focus clutch mechanism enables instant AF/MF switching and accurate manual focusing.

The LUMIX S PRO 16-35mm F4 also excels in video recording performance with a mechanism that suppresses focus breathing, which was a fatal problem in all interchangeable lenses designed for still image photography.

(*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.)

Specifications

• Closest Focusing Distance: 0.25m / 0.82ft

• Diagonal Angle of View: 107ã,œWide) - 63ã,œ(Tele)

• Filter Size: φ77mm

Focal Length: f=16-35mmMaximum Aperture: F4

Maximum Diameter: φ85mm / 3.34inch
Maximum Magnification: Approx.0.23x

• Minimum Aperture: F22

• Mount Type: L

• Optical Image Stabilizer: No

• Weight: approx.500g /17.63 oz (excluding lens cap, lens rear cap and lens

hood)