

## Panasonic LUMIX S-R24105

ProdCode: PANSR24105E

L-Mount 24-105mm Standard Zoom Lens

[Download Images] (.zip file)

## **Features**

- L-Mount 24-105mm Standard Zoom Lens
- Lumix S Camera Lens

24-105mm standard focal macro zoom F4 L-Mount for LUMIX S Series Full-Frame L-Mount digital mirrorless cameras.

• O.I.S. Stabilization

Complies with LUMIX camera body I.S.; 5-Axis Dual I.S. 2 [1] makes it possible to use 6-stop slower shutter speed [2]

• Lens Elements

16 lenses in 13 groups; 2 aspherical lenses and 2 ED (Extra-low Dispersion) lenses effectively suppress chromatic aberration and achieve high resolution.

Macro Lens

0.5x macro shooting with a minimum focusing distance of 0.3m so you can photograph small subjects at very close distances.

Rugged Lens Design

Dust/splash\*/freeze-resistant design withstands use under harsh conditions for high mobility.

The Panasonic LUMIX S-R24105 24-105mm F4 Macro Lens with O.I.S. is a versatile standard zoom lens covering wide-angle to medium-telephoto with high-descriptive performance across the entire zoom range. The LUMIX S Macro Lens enables 0.5x macro shooting with a minimum focus distance of 0.3m so you can photograph small subjects at very close distances. This Macro lens is compatible with the interchangeable Full Frame L-Mount.

The O.I.S. (Optical Image Stabilizer) in the lens effectively compensates for handshake movement, making it easy to shoot without a tripod. This Panasonic LUMIX lens offers high-precision Auto Focus to capture every photo opportunity. The focus clutch mechanism enables both instant AF/MF switching and accurate manual focusing. Focus breathing is suppressed making it an excellent choice for video recording.

Camera performance, lightweight construction, and Dust/Splash\*/Freeze-Resistant Design are some of the features you'll enjoy while shooting with the Panasonic LUMIX S Series lens.

DISCLAIMERS: [1] 5-Axis Dual I.S. 2 can be used with the camera LUMIX S1R and S1, as of February 1, 2019. [2] Based on the CIPA standard [Yaw/Pitch direction: focusing distance f=105mm, when LUMIX S1R is used.

## **Specifications**

• Closest Focusing Distance: 0.30m / 0.98ft

• Diagonal Angle of View: 84°(Wide) - 23°(Tele)

• **Dimensions:** Length: Approx. 118mm / 4.65" (from the tip of the lens to the base side of the lens mount)

• Filter Size: φ77mm

Focal Length: 24-105mm
 Geared Focus / Iris: No

• Lens Construction: 16 elements in 13 groups

• Lens Type: Zoom

• Maximum Aperture: F4.0

Maximum Diameter: φ84mm / 3.31"
Maximum Magnification: Approx. 0.5x

• Minimum Aperture: F22

• Mount Type: L

• No. Diaphragm Blades: 9 diaphragm blades

• Optical Image Stabilizer: Yes

• Weather Proof: Dust and Splash Resistant

 Weight: Approx. 680g / 23.99oz (excluding lens cap, lens rear cap and lens hood)