

## Panasonic LUMIX S-S85E

ProdCode: PANSS85E

Compact, lightweight LUMIX S 85mm F1.8 lens

[Download Images] (.zip file)

## **Features**

- Compact, lightweight LUMIX S 85mm F1.8 lens
- Mount: L-Mount
- Focal Length: f=85mm
- Aperture Type: 9 diaphragm blades / Circular aperture diaphragm
- Maximum Aperture: F1.8Minimum Aperture: F22
- Closest Focusing Distance: 0.8m/2.62ft
- Maximum Magnification: 0.13x
- Filter Size: ?67mm
- Diagonal Angle of View: 29°
- Lens Construction: 9 elements in 8 groups (2 ED lenses)
- Optical Image Stabilizer: No
- Dust and Splash Resistant: Yes\*
- Recommended Operating Temperature: -10oC to 40oC (14oF to 104oF)
- Max. Diameter: ?73.6mm / 2.90inch
- Overall Length: Approx. 82.0mm / 3.23inch (from the tip of the lens to the base side of the lens mount)
- Weight: Approx. 355g / 12.52oz (excluding lens cap, lens rear cap and lens hood)

*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with own	dust and

Comprising 9 elements in 8 groups, the use of 2 ED (Extra-low Dispersion) lenses effectively suppress both axial chromatic aberration and chromatic aberration of magnification.

Panasonic S Series lenses pursue the beauty of bokeh and the LUMIX S 85mm F1.8 provides smooth defocus gradation from the focus peak to the neighbouring area of the image as well as smooth, round bokeh of point light source without vignetting.

The LUMIX S 85mm F1.8 also excels in video recording performance with a mechanism that suppresses focus breathing. The filter diameter is 67 mm, with a 9-blade circular aperture diaphragm.

With its compact 355g (approx.) of light weight, the LUMIX S 85mm F1.8 is incredibly flexible. The rugged dust/splash-resistant\* design withstands use under harsh conditions even at 10 degrees below zero.

## In the box:

- Lens cap
- Lens rear cap
- Lens hood

